

BITEC® Beta Base is an oxidized (i.e. non-modified) bitumen fiberglass reinforced base sheet that can be used in APP and SBS modified bitumen and traditional built-up roof systems.

FEATURES & BENEFITS

BITEC Beta Base also provides the following features and benefits:

- Notably high breaking strength
- Ply strips are furnished for ease in alignment
- Meets ASTM D4601, Type II specifications
- Classified by Underwriters Laboratories in a variety of assemblies under File No. R13231

PACKAGING

Roll package: Two labeled plastic bands

Rolls per pallet: 20

Pallets per truckload (typical): 22

APPROVALS

UL Classified R13231 Membrane for Roofing Systems as to an External Fire Exposure Only 49S8

NEMO Certified D7447988J

STANDARD SPECIFICATION(S):

ASTM D4601, Type II

HUD MR No. 1229

APPLICATION



Beta Base can be mechanically attached, hot mopped in Type III or IV asphalt, or applied in approved BITEC elastomeric adhesives. Please refer to the BITEC Roofing Products Installer's Guide for detailed application guidelines.

As with any roofing project, good roofing practices should always be followed.

STORAGE & HANDLING

Store the Beta Base rolls with labels unbroken in a clean, dry, protected location and within the temperature range required to provide for proper application. Units should be stored inside and away from exposure to the elements until immediately

before use. Beta Base can be used during cold weather if care is taken to warm the rolls by storing them in a warehouse or contained area with an ambient temperature of at least 55°F (12.7°C).

PRECAUTIONS

Safety first! The roofing contractor and employees are the key to success regarding safety. Safety should always be first! Read all label information, SDS, and precautions before using. For safety information on our products, please visit www.bitec.com.

