

# ElastoTherm™ Max Roofing Insulation

## TECHNICAL PRODUCT INFORMATION



**BITEC® ElastoTherm Max is a closed cell polyisocyanurate thermal insulation panel with an integrally bonded reflective foil facer and is compatible with BITEC roof membranes and systems.**

### FEATURES & BENEFITS

BITEC ElastoTherm Max also provides the following features and benefits:

- Available in both Grade 2 (20 psi) and Grade 3 (25 psi) compressive strengths, tested per ASTM C 1289
- Manufactured in both 4' x 4' and 4' x 8' sizes
- Thicknesses of flat insulation between 1" to 4" - additional thicknesses may be available
- Manufactured using a CFC-free, HCFC-free, and HFC-free foam blowing technology that has zero ozone depletion potential (ODP) and virtually no global warming potential

### PACKAGING

Packaging: Shrink wrapped bundles on pallets

Pieces per pallet: Please refer to the table on the following page

Pallets per truckload (typical for 4'x8' pallets): 22-24

### APPROVALS

UL 1256 Insulated Metal Deck Constructions No. 120, 123, and 292

UL 790 Roofing Systems Classification

UL 263 Fire Resistance Classification

UL 1897 Uplift Resistance

FLORIDA PRODUCT APPROVAL FL 17989

FM Approved 4450 / 4470 (refer to RoofNav for specific details)

### APPLICATION

BITEC ElastoTherm Max roofing insulation can be installed as a part of many different roofing systems. Please refer to the BITEC Roofing Products Installer's Guide for detailed application guidelines.

Panels must be kept dry from storage through installation. Install only as much as can be covered with roofing that same day. When using multiple layers of insulation, joints should be staggered a minimum of 6" (15 cm) to prevent thermal bridging. Panels must be fitted neatly to the roof deck and with no more than a 1/4" (0.6 cm) gap around penetrations.

Panels should be abutted together and adjacent panels should have their joints staggered. New concrete decks must be fully hydrated and are no longer releasing moisture.

**As with any roofing project, good roofing practices should always be followed.**

### STORAGE & HANDLING


Store ElastoTherm panels flat and in a horizontal position to prevent damage, in the original pallet and shrink wrap, if possible. Store elevated (at least 3" / 7.6 cm) and covered to protect from environmental damage. Do not use wet or damaged panels. Refer to PIMA Tech Bulletin No. 109 for additional guidelines.

### PRECAUTIONS

Safety first! The roofing contractor and employees are the key to success regarding safety. Safety should always be first! Read all label information, SDS, and precautions before using. For safety information on our products, please visit [www.bitec.com](http://www.bitec.com).

# ElastoTherm™ Max Roofing Insulation

## TECHNICAL PRODUCT INFORMATION



Thermal and Packaging Data - Flat						
Thickness		LTTR Value	RSI	Pallet Quantity	Flute Spanability	
in	mm				in	mm
1.0	25.4	5.7	1.00	48	2.625	66.68
1.5	38.1	8.6	1.50	32	4.375	111.13
2.0	50.8	11.4	2.01	24	4.375	111.13
2.5	63.5	14.4	2.53	19	4.375	111.13
3.0	76.2	17.4	3.06	16	4.375	111.13
3.5	88.9	20.5	3.60	13	4.375	111.13
4.0	101.6	23.6	4.15	12	4.375	111.13

Technical Schedule		
Compressive Strength	20 psi (Grade 2)	ASTM D1621
Dimensional Stability	<2%	ASTM D2126
Water Absorption	<0.5%	ASTM C209
Vapor Transmission	<0.3 perms	ASTM E96
Flame Spread	<75	ASTM E84
Smoke Developed	<450	ASTM E84
Density	2.0 pcf	ASTM D1622

All information is given in good faith but normal tolerances of manufacture and testing will apply. BITEC reserves the right to improve and change its products at any time without prior notice or advice. The use of BITEC products is determined by local conditions and individual requirements of each contract. In consideration of the many factors involved, BITEC cannot be held responsible for the improper application of its products and for conditions beyond its control. All claims filed against BITEC warranties will be subject to the provisions set forth at the date of the warranty issuance, and any addendum thereto. Under no circumstances will BITEC be held liable for any damage, whether personal injury or property damage, which occur during or after the application of any BITEC products.

Copyright BITEC, Inc.  
Revision Date 12/2025



BITEC, Inc.  
PO Box 497  
#2 Industrial Park Dr  
Morrilton, AR 72110  
Phone: (800) 535-8597  
Fax: (501) 354-3019  
[www.bitec.com](http://www.bitec.com)

**BITEC**®

**WHEN QUALITY MATTERS™**