

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture
Product Name: MAC-300
Product Code: F02421

Intended Use of the Product

Asphalt-based, fibered aluminum coating. For professional use only

Name, Address, and Telephone of the Responsible Party

Manufacturer

BITEC, Inc.
#2 Industrial Park Drive
Morrilton, AR 72110
T-800-535-8597
F-501-354-3019
www.bitec.com

Emergency Telephone Number

Emergency Number: 1-800-535-8597

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Flam. Liq. 3	H226
Asp. Tox. 1	H304
Eye Irrit. 2A	H319
Mutagenicity, 1B	H340
Carc., 1B	H350
Reproductive Tox. 2	H361
Aquatic Acute 1	H400
Aquatic Chronic 2	H411

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

Hazard Statements (GHS-US)

- : Danger
- : H226 – Flammable liquid and vapor.
H304 – May be fatal if swallowed and enters airways
H319 – Causes serious eye irritation.
H332 – Harmful if inhaled.
H340 – May cause genetic defects.
H350 – May cause cancer.
H361 – Suspected of damaging fertility or the unborn child.
H400 – Very toxic to aquatic life.
H411 – Toxic to aquatic life with long lasting effects.
- Precautionary Statements (GHS-US)** :
- P201 – Obtain special instructions before use.
P202 – Do not handle until all safety precautions have been read and understood.
P210 – Keep away from heat/sparks/open flames/hot surfaces. –no smoking.
P233 – Keep container tightly closed.
P240 – Ground/bond container and receiving equipment.
P241 – Use explosion-proof electrical/ventilating/lighting equipment.
P242 – Use only non-sparking tools.
P243 – Take precautionary measures against static discharge.
P264 – Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 – Avoid release to the environment.
P280 – Wear protective gloves/protective clothing/eye protection/face protection.

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P353 – IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 – If exposed or concerned: Get medical advice/attention.
P331 – Do NOT induce vomiting.
P337+P313 – If eye irritation persists: Get medical advice/attention.
P370+P378 – In case of fire: use appropriate media to extinguish.
P391 – Collect spillage.
P403+P235 – Store in a well-ventilated place. Keep cool.
P405 – Store locked up.
P501 – Dispose of contents/container according to local, regional, national, and international regulations.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Petroleum Asphalt	(CAS No) 8052-42-4	30-35	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Carc. 2, H351
Solvent Naphtha (petroleum), light arom.	(CAS No) 64742-95-6	20-25	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336
Stoddard Solvent	(CAS No) 8052-41-3	20-30	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Aluminum	(CAS No) 7429-90-5	20-25	Comb. Dust, H232 Flam. Sol. 1, H228 Water-react. 2, H261
Naphtha, petroleum, hydrodesulfurized, heavy	(CAS No) 64742-82-1	8-10	Flam. Liq. 1, H224 Skin irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 Repr. 2, H361 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
1,3,5-Trimethylbenzene	(CAS No) 108-67-8	1-2	Flam. Liq. 3, H226 Acute Tox. 4, H334 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
Benzene, 1,2,4-trimethyl-	(CAS No) 95-63-6	1-2	Flam. Liq. 3, H226 Acute Tox. 4, H332

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

			Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Cellulose Full text of H-Phrases: See Section 16	(CAS No) 9004-34-6	2.5-3.5	Comb. Dust, H232

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.

First-aid Measures After Inhalation: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention. Asthmatic type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic.

First-aid Measures After Skin Contact: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

First-aid Measures After Eye Contact: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

First-aid Measures After Ingestion: If swallowed, do NOT induce vomiting. Give victim two glasses (16 ounces) of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms/Injuries: Causes eye irritation. Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes eye irritation.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause cancer. May cause heritable genetic damage. Suspected of damaging fertility or the unborn child.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, carbon dioxide, dry chemical, or foam.

Unsuitable Extinguishing Media: Do not use extinguishing media containing water. Water or foam may cause frothing. Use of water on product above 100 °C (212 °F) can cause product to expand with explosive force.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: This product is flammable.

Explosion Hazard: May form flammable/explosive vapor-air mixture.

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Advice for Firefighters

Firefighting Instructions: Exercise caution when fighting any chemical fire.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂), Hydrocarbons.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapor, mist, spray. Use only outdoors or in a well-ventilated area. Handle in accordance with good industrial hygiene and safety practice.

For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area. Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Prevent entry to sewers and public waters.

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and Material for Containment and Cleaning Up

For Containment: Contain with inert absorbent material.

Methods for Cleaning Up: Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder). Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Precautions for Safe Handling: Handle empty containers with care because residual vapors are flammable.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Keep in properly labeled containers. Keep tightly closed in a cool dry place. Use explosion-proof electrical, lighting, and ventilating equipment.

Incompatible Materials: Strong acids, strong bases. Strong oxidizers.

Storage Area: Store locked up. Store in a well-ventilated place.

Specific End Use(s)

Aluminum Roof Coating

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Petroleum Asphalt (8052-42-4)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	5 mg/m ³
Mexico	OEL TWA (mg/m ³)	5 mg/m ³
Mexico	OEL STEL (mg/m ³)	10 mg/m ³
Ontario	OEL TWA (mg/m ³)	0.5 mg/m ³

Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Mexico	OEL TWA (mg/m ³)	10 mg/m ³ (dust)
Ontario	OEL TWA (mg/m ³)	1 mg/m ³ (dust)

Benzene, 1,2,4-trimethyl- (95-63-6)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm

1,3,5-trimethylbenzene (108-67-8)		
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	25 ppm

Cellulose (9004-34-6)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL TWA (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
Mexico	OEL STEL (mg/m ³)	20 mg/m ³

MAC-300

Safety Data Sheet


According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Stoddard Solvent (8052-41-3)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³
USA IDLH	US IDLH (mg/m ³)	20000 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
Mexico	OEL TWA (mg/m ³)	523 mg/m ³
Mexico	OEL STEL (mg/m ³)	1050 mg/m ³
Ontario	OEL TWA (mg/m ³)	525 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapors may be released. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Hand Protection: Protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Other Information: When using, do not eat, drink, or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Silver
Odor	: Petroleum Distillates
Flash Point	: 105°F (41°C)
Auto-ignition Temperature	: 540°F (282°C)
Lower Flammable Limit	: 0.8%
Upper Flammable Limit	: 6.0%
Vapor Pressure	: 5mmHg
Specific Gravity	: 0.95
Solubility	: Insoluble
Volatile Organic Compounds	: 400 g/L
Volatiles	: 44-50%

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts with strong oxidants causing fire and explosion hazard.

Chemical Stability: Product is stable under recommended handling and storage conditions (see Section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

Information On Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: May cause genetic defects.

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Teratogenicity: Not available

Carcinogenicity: May cause cancer.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Specific Target Organ Toxicity (Single Exposure): Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: May be fatal if swallowed and enters airways.

Chronic Symptoms: May cause cancer. May cause heritable genetic damage. Suspected of damaging fertility of the unborn child.

Information on Toxicological Effects – Ingredient(s)

LD50 and LC50 Data

Petroleum Asphalt (8052-42-4)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg

Solvent Naphtha, petroleum, light aromatic (64742-95-6)	
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	3400 ppm (Exposure time: 4 h)

Stoddard Solvent (8052-41-3)	
LD50 Oral Rat	>5 g/kg Behavioral somnolence
LD50 Dermal Rabbit	> 3 mg/kg

Benzene, 1,2,4-trimethyl- (95-63-6)	
LD50 Oral Rat	6000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
LC50 Inhalation Rat	18 g/m ³ (Exposure time: 4 h)

1,3,5-trimethylbenzene (108-67-8)	
LC50 Inhalation Rat	24 g/m ³ (Exposure time: 4 h)

Cellulose (9004-34-6)	
LD50 Oral Rat	>5000 mg/kg
LD50 Dermal Rabbit	>2000 mg/kg
LC50 Inhalation Rat	>5800 mg/m ³ (Exposure time: 4 h)

Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1)	
LD50 Oral Rat	>5000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg

Carcinogenicity Data:

Petroleum Asphalt (8052-42-4)	
IARC Group	2B
National Toxicity Program (NTP) Status	Twelfth Report – Items under consideration

Quartz, silica (14808-60-7)	
IARC Group	1
National Toxicity Program (NTP) Status	Known Human Carcinogens

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Ingredients

1,3,5-trimethylbenzene (108-67-8)	
LC50 Fish 1	3.48 mg/L (Exposure time: 96 h – Species: Pimephales promelas)

Stoddard Solvent (8052-41-3)	
-------------------------------------	--

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

EC50 Daphnia 1	0.42 mg/L
----------------	-----------

Solvent Naphtha, petroleum, light aromatic (64742-95-6)	
LC50 Fish 1	9.22 mg/L (Exposure time: 96 h – Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/L (Exposure time: 48 h – Species: Daphnia magna)

Benzene, 1,2,4-trimethyl- (95-63-6)	
LC50 Fish 1	7.5 mg/L (Exposure time: 96 h)

Persistence and Degradability

Not available

Bioaccumulative Potential – Product

Not available

Bioaccumulative Potential – Ingredients

Petroleum Asphalt (8052-42-4)	
BCF Fish 1	No bioaccumulation expected
Log Pow	> 6

Benzene, 1,2,4-trimethyl- (95-63-6)	
Log Pow	3.63

Stoddard solvent (8052-41-3)	
Log Pow	3.16 (Octanol/water partition coefficient 3.16/7.06)

Mobility in Soil

No additional information available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Additional Information: Prevent runoff from entering drains, sewers, or waterways.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name : Non-Regulated Material per 49 CFR 173.150(f)

In Accordance with IMDG

Proper Shipping Name : Tars, liquid

Hazard Class : 3

Identification Number : UN1999

Packing Group : III



In Accordance with IATA

Proper Shipping Name : Tars, liquid

Hazard Class : 3

Identification Number : UN1999

Packing Group : III



In Accordance with TDG

Proper Shipping Name : Not Regulated

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes
Fire hazard
Immediate (acute) health hazard
Delayed (chronic) health hazard

Petroleum Asphalt (8052-42-4)
Listed on the United States TSCA (Toxic Substances Control Act) Inventory

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Solvent Naphtha, petroleum, light aromatic (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

Benzene, 1,2,4-trimethyl- (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 – Emission Reporting	1.0%

1,3,5-trimethylbenzene (108-67-8)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
EPA TSCA Regulatory Flag	T – T – indicates a substance that is the subject of a Section 4 test rule under TSCA.

Cellulose (9004-34-6)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

Aluminum (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Listed on United States SARA Section 313	
SARA Section 313 – Emission Reporting	1.0% (dust or fume only)

Naphtha, petroleum, hydrodesulfurized heavy (64742-82-1)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

Stoddard Solvent (8052-41-3)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

US State Regulations

Petroleum Asphalt (8052-42-4)	
RTK – U.S. – Massachusetts – Right To Know List	
RTK – U.S. – New Jersey – Right To Know Hazardous Substance List	
RTK – U.S. – Pennsylvania – RTK (Right To Know) List	

Benzene, 1,2,4-trimethyl- (95-63-6)	
RTK – U.S. – Massachusetts – Right To Know List	
RTK – U.S. – New Jersey – Right To Know Hazardous Substance List	
RTK – U.S. – Pennsylvania – Right To Know Environmental Hazard List	
RTK – U.S. – Pennsylvania – RTK (Right To Know) List	

Stoddard Solvent (8052-41-3)	
RTK – U.S. – Massachusetts – Right To Know List	
RTK – U.S. – New Jersey – Right To Know Hazardous Substance List	
RTK – U.S. – Pennsylvania – RTK (Right To Know) List	

1,3,5-trimethylbenzene (108-67-8)	
RTK – U.S. – Massachusetts – Right To Know List	

Cellulose (9004-34-6)	
RTK – U.S. – Massachusetts – Right To Know List	
RTK – U.S. – New Jersey – Right To Know Hazardous Substance List	
RTK – U.S. – Pennsylvania – RTK (Right To Know) List	

Aluminum (7429-90-5)	
RTK – U.S. – Massachusetts – Right To Know List	
RTK – U.S. – New Jersey – Right To Know Hazardous Substance List	
RTK – U.S. – Pennsylvania – Right To Know Environmental Hazard List	
RTK – U.S. – Pennsylvania – RTK (Right To Know) List	

MAC-300

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Canadian Regulations

Petroleum Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List) Inventory

1,3,5-trimethylbenzene (108-67-8)

Listed on the Canadian DSL (Domestic Substances List) Inventory

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1%

WHMIS Classification Class B Division 3 – Combustible Liquid

Stoddard Solvent (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List) Inventory

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

WHMIS Classification Class B Division 3 – Combustible Liquid
Class D Division 2 Subdivision B – Toxic material causing other toxic effects

Solvent Naphtha, petroleum, light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List) Inventory

Benzene, 1,2,4-trimethyl- (95-63-6)

Listed on the Canadian DSL (Domestic Substances List) Inventory

Naphtha, petroleum, hydrodesulfurized, heavy (64742-82-1)

Listed on the Canadian DSL (Domestic Substances List) Inventory.

WHMIS Classification Class D Division 2 Subdivision A – Very toxic material causing other toxic effects
Class D Division 2 Subdivision B – Toxic material causing other toxic effects
Class B Division 2 – Flammable Liquid

Aluminum (7429-90-5)

Listed on the Canadian DSL (Domestic Substances List) Inventory

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1%

WHMIS Classification Class B Division 6 – Reactive Flammable Material
Class D Division 4 – Flammable Solid

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 12/12/2025

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

Bitec, Inc.

#2 Industrial Park Drive

Morrilton, AR 72110

T-800-535-8597

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2018 & WHMIS