

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: ElastoPav-AP - All-Purpose Roofing Sealant

Product Code: F022101

Intended Use of the Product

Roofing Sealant

Name, Address, and Telephone of the Responsible Party

Manufacturer

BITEC, Inc.

#2 Industrial Park Drive

Morrilton, AR 72110

T-800-535-8597

F-501-354-3019

www.bitec.com

Emergency Telephone Number

Emergency Number: 1-800-535-8597

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2A H315

Skin sens. 1 H317

STOT RE 2 H373

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Warning

Hazard Statements (GHS-US)

: H315 – Causes serious eye irritation

H317 – May cause an allergic skin reaction

H373 – May cause damage to organs through prolonged or repeated exposure

Precautionary Statements (GHS-US)

: Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust, fume, gas, mist, vapors and spray

Wear protective gloves, eye protection and face protection

Get medical advice/attention if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice and attention

IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice and attention

Wash contaminated clothing before reuse

Dispose of contents and container to an approved waste disposal plant

May be harmful in contact with skin. May be harmful if inhaled.

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US)

No data available

Disclaimer ATTENTION! Some of the additives disclosed in Section 3 such as Carbon Black, Crystalline Silica, and or Titanium Dioxide are regulated by California Proposition 65 as carcinogens when they are in the form of “airborne, unbound particles of respirable size.” Since the disclosed materials are bound in the polymer matrix, they will not be available as an airborne hazard (dust, mist, or spray) under normal conditions of use. Therefore, this product does not present a respiration hazard as outlined by the Prop 65 regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

ElastoPav-AP - All-Purpose Roofing Sealant

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Mixture

Name	Product identifier	% (w/w)
Calcium Carbonate	471-34-1	20 - 40
Limestone	1317-65-3	10 - 20
Titanium Dioxide	13463-67-7	1 - <5
Stearic Acid	57-11-4	1 - <5
Proprietary Dehydration Agent	Trade secret	1 - <5
Proprietary Adhesion Promoter	Trade secret	1 - <5
Crystalline Silica	14808-60-7	<0.1

Full text of H-Phrases: See Section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

First-aid Measures General: Show this material safety data sheet to the doctor in attendance.

First-aid Measures After Inhalation: Remove to fresh air.

First-aid Measures After Skin Contact: Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

First-aid Measures After Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.

First-aid Measures After Ingestion: Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician.

Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media: Do not use water jet. Use of heavy stream of water may spread fire.

Special Hazards Arising from the Substance or Mixture

Product is or contains a sensitizer. May cause sensitization by skin contact. Containers may explode when heated.

Advice for Firefighters

Protection During Firefighting: Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection. Use proper PPE.

Emergency Procedures: Ventilate area. Evacuate unnecessary personnel. Eliminate ignition sources. Stop leak if safe to do so. Prevent entry to sewers and public waters.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and Material for Containment and Cleaning Up

For Containment: Absorb and/or contain spill with inert material.

Methods for Cleaning Up: Collect spillage. Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

ElastoPav-AP - All-Purpose Roofing Sealant

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Precautions for Safe Handling

Precautions for Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Contaminated work clothing should not be allowed out of the workplace.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Keep containers tightly closed in a dry, cool and well-ventilated place.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Calcium Carbonate 471-34-1	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Titanium Dioxide 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ fine scale respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Stearic Acid 57-11-4	TWA: 10 mg/m ³ inhalable particulate matter TWA: 3 mg/m ³ respirable particulate matter	-	-
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

Chemical name	Alberta	British Columbia	Ontario	Quebec
Calcium Carbonate 471-34-1	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³ STEL: 20 mg/m ³	-	TWA: 10 mg/m ³
Limestone 1317-65-3	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³ STEL: 20 mg/m ³	-	TWA: 10 mg/m ³
Titanium Dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	-	TWA: 10 mg/m ³
Stearic Acid 57-11-4	-	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³

ElastoPav-AP - All-Purpose Roofing Sealant

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

Proprietary Dehydration Agent	-	-	STEL: 10 ppm STEL: 60 mg/m ³	-
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.10 mg/m ³	TWA: 0.10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Showers. Eyewash stations. Ventilation systems.

Personal Protective Equipment

Hand Protection: Wear suitable gloves

Eye Protection: Chemical goggles or safety glasses with side shields.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required

Other Information: When using, avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Paste
Odor	: Not applicable
Flash Point	: Not determined
Vapor Pressure	: Not determined
Specific Gravity	: Not determined
Solubility	: Not determined
Volatile Organic Compounds	: Not determined

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Product is stable under recommended handling and storage conditions (see Section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: None known based on information supplied.

Incompatible Materials: None known based on information supplied.

Hazardous Decomposition Products: None known based on information supplied.

SECTION 11: TOXICOLOGICAL INFORMATION

Information On Toxicological Effects – Product

Product

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May be harmful if inhaled.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation. May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 18,716.00 mg/kg

ATEmix (dermal) 4,049.70 mg/kg

ATEmix (inhalation-gas) 99,999.00 ppm

ATEmix (inhalation-dust/mist) 102.40 mg/l

ATEmix (inhalation-vapor) 366.90 mg/l

Unknown acute toxicity

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Calcium Carbonate	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h

ElastoPav-AP - All-Purpose Roofing Sealant

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

471-34-1			
Titanium Dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	= 5.09 mg/L (Rat) 4 h
Stearic Acid 57-11-4	= 4600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Proprietary Dehydration Agent	= 7340 µL/kg (Rat)	= 3.54 mL/kg (Rabbit)	= 16.8 mg/L (Rat) 4 h
Proprietary Adhesion Promoter	= 2413 mg/kg (Rat)	> 2009 mg/kg (Rabbit)	1.49 - 2.44 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium Dioxide 13463-67-7	A3	Group 2B	-	X
Crystalline Silica 14808-60-7	A2	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology – General: Very toxic to aquatic life with long lasting effects.

Stearic Acid	
LC50 Brachydanio rerio	<3000 mg/L 96 hours
LC50 Danio rerio	>1000 mg/L 96 hours

Proprietary Dehydration Agent	
LC50 Oncorhynchus mykiss	191 mg/L 96 hours

Bioaccumulative Potential

Stearic Acid	
Partition coefficient	3.3

Mobility in Soil

No additional information available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international

ElastoPav-AP - All-Purpose Roofing Sealant

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

regulations.

Additional Information: Prevent runoff from entering drains, sewers, or waterways.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :

In Accordance with IMDG

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :
Marine pollutant : No

In Accordance with IATA

Proper Shipping Name : Not regulated
Hazard Class :
Identification Number :
Packing Group :

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	All ingredients are listed or exempt.
DSL/NDSL	All ingredients are listed or exempt.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
IECSC	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AIIC	Contact supplier for inventory compliance status.
NZIoC	Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AIIC - Australian Inventory of Industrial Chemicals

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR

ElastoPav-AP - All-Purpose Roofing Sealant

Safety Data Sheet

According to Federal Register/Vol. 77, No. 58/Monday, March 26, 2012/Rules and Regulations

122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Titanium Dioxide - 13463-67-7	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen

See disclaimer in section 2.

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 03/27/2026

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

BITEC, Inc.
#2 Industrial Park Drive
Morrilton, AR 72110
T-800-535-8597

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2019 & WHMIS