

Weathered Membrane Cleaner

TECHNICAL PRODUCT INFORMATION



STRONGHOLD™

StrongHold Weathered Membrane Cleaner is used for cleaning the surfaces of TPO and EPDM single ply membranes, both new and in-service, prior to heat-welding or installation of primers, self-adhering tapes, and flashings.

FEATURES & BENEFITS

StrongHold Weathered Membrane Cleaner also provides the following features and benefits:

- Provides a clean surface, easily removing dirt and other contaminants
- Prepares both aged and new TPO for heat-welding
- Prepares EPDM for self-adhering tapes and primers

PACKAGING

Packaging: 1-gallon cans, 4 cans / case

Quantity per pallet: 36

Pallets per truckload (typical): 18

APPLICATION

Product application should be suspended immediately and our technical service personnel contacted if the results being obtained are less than desirable.

Remove as much loose dirt and debris prior to using StrongHold Weathered Membrane Cleaner. More extreme conditions may require cleaning more thoroughly with water and a low sudsing detergent. When cleaned in this manner, always be sure to rinse thoroughly with clean water and permit to dry completely.

To clean a specific area, saturate a clean rag with StrongHold Weathered Membrane cleaner and scrub the area in a circular motion. Change rags frequently / as needed and continue to clean the area until the surface is visually clean with a consistent color. Allow the cleaner to dry completely before proceeding.

Coverage rates for StrongHold Weathered Membrane Cleaner can vary drastically, depending on the condition of the existing roof and amount of flashing details present.

Specific application methods may vary, depending on the roof system being installed, as well as the substrate and type of insulation being adhered. Please refer to the BITEC Roofing Products Installer's Guide for detailed application guidelines.

As with any roofing project, good roofing practices should always be followed.

STORAGE & HANDLING

Store materials locked up and in a well-ventilated, dry, and temperature conditioned location. Keep containers tightly closed to avoid contamination.

PRECAUTIONS

StrongHold Weathered Membrane Cleaner is extremely flammable - make sure to read all safety information prior to use and keep the material away from all sources of heat, flame, or sparks.

Safety first! Read all label information, SDS, and precautions before using. For safety information on our products, please visit www.bitec.com.

All information is given in good faith but normal tolerances of manufacture and testing will apply. BITEC reserves the right to improve and change its products at any time without prior notice or advice. The use of BITEC products is determined by local conditions and individual requirements of each contract. In consideration of the many factors involved, BITEC cannot be held responsible for the improper application of its products and for conditions beyond its control. All claims filed against BITEC warranties will be subject to the provisions set forth at the date of the warranty issuance, and any addendum thereto. Under no circumstances will BITEC be held liable for any damage, whether personal injury or property damage, which occur during or after the application of any BITEC products.

Copyright BITEC, Inc.
Revision Date 01/2026



BITEC, Inc.
PO Box 497
#2 Industrial Park Dr
Morrilton, AR 72110
Phone: (800) 535-8597
Fax: (501) 354-3019
www.bitec.com

BITEC®

WHEN QUALITY MATTERS™